



EE 46 Pin 500V Heavy Duty Connector Female Insert

OUKERUI is a Chinese manufacturer and supplier with many years of production of EE 46 Pin 500V Heavy Duty Connector Female Insert cover. We look forward to establishing friendly and cooperative relationship with your company with high quality products. reasonable price and thoughtful service and work together to create a better tomorrow



Product Description

High quality EE 46 Pin 500V Heavy Duty Connector Female Insert is supplied by the Chinese manufacturer OUKERUI. Buy MEE 46 Pin 500V Heavy Duty Connector Female Insert with high quality and low price. Factory Sourcing Heavy Duty Connector for Automatic Industry, Widely Used for Wire Harness. IP65 Water Proof Heavy Duty Connector for Various Harsh Enviroments to Equal to Harting.

Product Description

EE 46 Pin 500V Heavy Duty Connector Female Insert is a Heavy Duty Connector manufacturer with TUV audit. We also have CE, UL, EAC certified high performance connectors. ISO quality management system. Patent configuration, easy installation, quick installation. Personalized interfaces for different scenarios. High quality raw material guarantee. Create more environmentally friendly products.

Basic Info.

Model NO.	HZW-HEE-046FC
Contacts Surface Treatment	Silver/Glod Plated
Housing Material	Die-Casting Aluminum Alloy
Working Environments	IP65 for Various Harsh Environments
Contact Cost	Pay Additional Cost for Crimp Contacts
Specification	CE, UL, ROHS



Origin	China
Production Capacity	3000pieces Per Day
Certification	UL
Contact Material	Copper
Housing Coating	Anti-Corrosion Powder Spray
Crimp Tooling	Available
Transport Package	Poly bag and Double Cartons
Trademark	Oukerui
HS Code	8536900000

SPECIFICATION


Model No.	HZW-HEE-046FC
Terminal type	Crimp Terminal
Housings material	Dia casting aluminum alloy
Working Voltage	500V
Rated Impulse Voltage	6KV
International protection(IP) grade	IP65
Flammability	V0
Mechanical Life Span	Min 500 times
Warranty	1 Year
Gender type	Female
Contacts' surface processing	Silver or Gold Plated
Mounting type	Bulkhead/Surface/ cable to cable
Insert Block	Top grade PC
Working Current	16A
Temperature Bearing Range	-40° C~+125° C
Pollution Degree	3
Transport packing	Carton



SPECIFICATION OF CONTACT

Material	Copper Alloy
Terminal	Screw/Crimp Terminal
Surface Treatment	Silver/Gold Plated
Wire Gauge	0.14-4.0mm ² (AWG26-14)
Stripping length	7.5mm

EE 46 Pin 500V Heavy Duty Connector Female Insert are extensively used in equipment that require electrical and signal connections, such as mold machinery, construction machinery, textile machinery, transportation technology, electric energy, electric locomotives and so on various need electrical and petrochemical equipment.





www.oukeruiconnector.com

上壳
Hoods



母插体
Female insert




公插体
Male insert




下壳
Housings







● 开孔安装/Bulkhead mounting
侧面进线/Side entry




● 开孔安装/Bulkhead mounting
顶部进线/Top entry




● 表面安装/Surface mounting
顶部进线/Top entry



● 表面安装/Surface mounting
侧面进线/Side entry



● 电缆对接/Cable to Cable
侧面进线/Side entry



● 电缆对接/Cable to Cable
顶部进线/Top entry